

# Yuasa Technical Data Sheet



## Yuasa NPL200-6 Industrial VRLA Battery

### Specifications

Nominal voltage (V)	6
20-hr rate Capacity to 10.5V at 20°C (Ah)	200
10-hr rate Capacity to 10.8V at 20°C (Ah)	176

### Dimensions

Length (mm)	398 (±0.7)
Width (mm)	176 (±0.5)
Height (mm)	250 (±0.7)
Mass (kg)	39

### Terminal Type

Threaded terminal - (M=Male or F=Female)	M10 LUG
Torque (Nm)	16.5

### Operating Temperature Range

Storage (in fully charged condition)	-20°C to +50°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C

### Storage

Capacity loss per month at 20°C (% approx.)	3
---	---

### Case Material

Standard	ABS (UL94:HB)
FR version available	UL94:V0

### Charge Voltage

Float charge voltage at 20°C (V)/Block	6.825 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	7.26 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4

### Charge Current

Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	50

### Maximum Discharge Current

1 second (A)	1500
1 minute (A)	600

### Impedance


Measured at 1 kHz (mΩ)	1.3
------------------------	-----

### Design Life & Approvals

EUROBAT Classification: Long life	10 to 12
Yuasa design life at 20°C (yrs)	up to 10



### Layout



### 3rd Party Certifications

ISO9001 - Quality Management Systems  
UNDERWRITERS LABORATORIES Inc.

## Safety

### Installation

Can be installed and operated in any orientation except permanently inverted.

### Handles

Batteries must not be suspended by their handles (where fitted).

### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

### Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.



www.akkumanufaktur.at

Data Sheet generated on 18/12/2017 - E&OE

The world's leading battery manufacturer

www.yuasaeurope.com

